



Water Heater Appliance Kit Specifications

Application

LeakSmart® Water Heater Leak Detection & Shut-Off Valve detects leaks and shuts off your water heater supply line in less than 5 seconds, protecting you from devastating water damage. Plus, it alerts you when detecting water leaks with audible and visible alarms. The valve is installed on the water heaters incoming cold supply. Everything is pre-wired to simplify the installation.

Additional Applications - Water Softeners

Features

Full port valves
Quick connect wiring
AC power with battery back-up
LED status light, visual alarm
Audible alarm
Alarm mute
3 LED status lights
Self test feature
Low voltage
Output trigger

Product Specifications

Max. operating pressure: 150 PSI
Max. ambient temperature: 130° F (54° C)
Min. water temperature: 33° F (1° C)
Max. water temperature: 190° F (88° C)

Valve connection type: NPT

Input AC Voltage: 110 to 240 VAC, 50/60 Hz

DC Output: 9 Volt


<u>Material</u>

Control panel: High performance engineered

polymer

Valve: Lead free brass








* Dimensions for reference purposes only

Dimensions

Valve	Α	В
3/4"	3.42	3.19
1/2"	3.73	3.42
1"	4.1	3.78



^{*} Included in kit, additional sensors sold separately. Item#8820700