

# HPZC10\*

# HONEYWELL HYDRONIC PRO CONTROLLER

# SUBMITTAL SHEET

Job Name	
Engineer	
Mechanical	
Contractor	
Contractor's P.O. No.	
Representative	
Notes	

Model(s)			
HPZC103	Qty.	Notes	
HPZC104	Qty.	Notes	
HPZC105	Qty.	Notes	
HPZC106	Qty.	Notes	
Approval			
Service			
Tag No.		 	



# **APPLICATION**

Honeywell's Hydronic Zoning Panels are the new standard for Hydronic controls, providing simplified setup and wiring for quick installation.

#### **FEATURES**

- Familiar Setup
- Flexible mounting
- Color coded wiring and terminals
- Simple layout cover
- Hinged door
- Integrated and visible LED panel
- Works with power stealing stats without the need of an additional resistor
- Auto-resettable fuses as well as backup glass fuses for double protection
- High output transformers for more power
- 5-year warranty

# INCLUDED IN THE BOX

- Zoning Panel
- Mounting Hardware (3 Screws and 3 Wall Anchors) 2, 2-Amp Fuses
- Spare Status Label (French)
- Install Manuals (English & French)

# **SPECIFICATIONS**

Product 7	Zones	Transformers <sup>1</sup>	Input Power	Electrical Rating for Main Burner, End Switch Burner, and Zones <sup>2</sup>	Electrical Rating for Pump End Switch and Priority Pump	Priority Zone Control	Type 1 Enclosure		
							Width	Height	Depth
HPZC103	3	1	120 VAC/60/1, 1.0 A	24 VAC, 1 A	1/3HP 120 VAC, 5 A	Yes	10-1/4"	7-1/2"	2-1/8"
HPZC104	4	1	120 VAC/60/1, 1.2 A	24 VAC, 1 A	1/3HP 120 VAC, 5 A	Yes	10-1/4"	7-1/2"	2-1/8"
HPZC105	5	2	120 VAC/60/1, 1.5 A	24 VAC, 1 A	1/3HP 120 VAC, 5 A	Yes	11-3/4"	7-1/2"	2-1/8"
HPZC106	6	2	120 VAC/60/1, 1.8 A	24 VAC, 1 A	1/3HP 120 VAC, 5 A	Yes	11-3/4"	7-1/2"	2-1/8"

 $<sup>^{1}\</sup>mbox{Each}$  transformer is protected with a 2 Amp replaceable fuses.

<sup>&</sup>lt;sup>2</sup>Transformers have a Class 2 output and are rated for 24 VAC, 40VA at 25C. It is up to the installer to ensure that the 40VA per transformer rating is not exceeded.