P643A Pressuretrol[™] Controller

SPECIFICATION DATA



FEATURES

- Adjustable setpoint
- Adjustable differential
- Heavy duty switch
- Integral gage connection

GENERAL

The P643A is used for Pneumatic-Electric relay applications in HVAC systems.



DESCRIPTION

The P643A is used for Pneumatic-Electric relay applications in HVAC systems.

SPECIFICATIONS

Model: P643A

Setpoint Range: 0 to 22.5 psi (0 to 155 kPa)

Switching:

Spdt Makes R to W on pressure rise Makes R to B on pressure fall

Differential: Adjustable, 3 to 13 psi (20 to 90 kPa)

Maximum Safe Air Pressure: 25 psi (175 kPa)

Adjustment Means: Thumbwheels under cover

Electrical Ratings (Amperes):

	120 Vac	208 Vac	240 Vac	277 Vac	480 Vac
Full Load	8.0	5.1	5.1	—	3.5
Locked Rotor	48.0	30.6	30.6	—	21.0
Resistance Load	17.0	17.0	17.0	17.0	10.0

125VA at 277 Vac pilot duty.


Air Connection:

Compression fitting for 1/4 in. O.D. tubing

Mounting:

Holes in back of case

Dimensions:



P643A Dimensions in Inches (Millimeters)

Finish: Cover: gray enamel Case: zinc plate

Ambient Temperature Limits:

-30 to 125F (-34 to 52C)

Approvals:

UL and C. S. A. listed

By using this Honeywell literature, you agree that Honeywell will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Honeywell, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.

Home and Building Control Honeywell Inc. Honeywell Plaza P.O. Box 524 Minneapolis MN 55408-0524

Honeywell Latin American Division Miami Lakes Headquarters 14505 Commerce Way Suite 500 Miami Lakes FL 33016 Home and Building Control Honeywell Limited-Honeywell Limitée 155 Gordon Baker Road North York, Ontario M2H 2C9

Honeywell Europe S.A. 3 Avenue du Bourget B-1140 Brussels Belgium Honeywell Asia Pacific Inc. Room 3213-3225 Sun Hung Kai Centre No. 30 Harbour Road Wanchai Hong Kong



