



Jones Stephens Corp.

BALL VALVES

PVC BALL VALVES


- One piece body construction
- EPDM seats and o-rings
- Working pressure 150 psi at 73° F
- Quarter turn operation
- Not for compressed air
- Ideal for swimming pools, irrigation and water supply uses
- Solvent ends comply with ASTM D 2466
- Threaded ends comply with ANSI B2.1
- Standard port
- For cold water lines
- Large flow opening

PART NO.	SIZE	CTN. QTY.	LIST PRICE
SOLVENT END			
B90-050	½"	100	3.51
B90-075	¾"	100	3.99
B90-100	1"	100	5.50
B90-125	1 ¼"	100	7.61
B90-150	1 ½"	48	12.98
B90-200	2"	24	16.47
B90-250	2 ½"	12	33.59
B90-300	3"	12	65.85
B90-400	4"	6	118.45
THREADED ENDS			
B91-050	½"	100	3.70
B91-075	¾"	100	4.24
B91-100	1"	100	5.70
B91-125	1 ¼"	100	7.99
B91-150	1 ½"	48	13.66
B91-200	2"	24	17.34
B91-250	2 ½"	12	35.36
B91-300	3"	12	69.32
B91-400	4"	6	124.68



CPVC BALL VALVES

- NSF approved!
- Standard port
- For use on CPVC tubing size (OD)
- Teflon seats
- EPDM o-rings
- One piece body construction
- Large flow opening
- For hot or cold water lines up to 100 psi at temperatures up to 180° F
- Solvent ends comply with ASTM D2846
- Quarter turn operation



PART NO.	SIZE	CTN. QTY.	LIST PRICE
B92-050	½" (¾" OD)	100	6.90
B92-075	¾" (1" OD)	100	8.45