


## 0

 $\succ$ 

## **MOUNTING TRACK**

## MT212 Series

2.75" Wide Mounting Track for Relays, Current Sensors, and Power Supplies



## **SPECIFICATIONS**

Flame Rated: 94-5V

- Approvals: UL Component Recognized, USA & Canada CE, RoHS
- Mounting: MT212 Series track can be screw-mounted to any flat surface to provide mounting for 2.75" wide track-mountable relays, current sensors, or power supplies.

| 0         |       |  |
|-----------|-------|--|
| MT212-6 C | E<br> |  |
| 0         |       |  |
|           |       |  |
|           |       |  |
|           |       |  |



| MT212 SERIES SELECTION GUIDE |       |        |                               |  |
|------------------------------|-------|--------|-------------------------------|--|
| Model #                      | Width | Length | Distance Between Hole Centers |  |
| MT212-2                      | 2.75″ | 2.00″  | 2.00" Center to Center        |  |
| MT212-4                      | 2.75″ | 4.00″  | 2.00" Center to Center        |  |
| MT212-6                      | 2.75″ | 6.00″  | 2.00" Center to Center        |  |
| MT212-8                      | 2.75″ | 8.00″  | 2.00" Center to Center        |  |
| MT212-12                     | 2.75″ | 12.00″ | 2.00" Center to Center        |  |
| MT212-18                     | 2.75″ | 18.00″ | 2.00" Center to Center        |  |
| MT212-24                     | 2.75″ | 24.00″ | 2.00" Center to Center        |  |
| MT212-48                     | 2.75″ | 48.00″ | 2.00" Center to Center        |  |