


 $\succ$ 

# **MOUNTING TRACK**

MT4 Series 4.00° Wide Mounting Track for Relays, Current Sensors, and Power Supplies



## **SPECIFICATIONS**

### Flame Rated: 94-5V

- Approvals: UL Component Recognized, USA & Canada CE, RoHS
- Mounting: MT4 Series track can be screw-mounted to any flat surface to provide mounting for 4.00" wide track-mountable relays, current sensors, or power supplies.

| MIT4-5<br>IIII - 5<br>IIIII - 5<br>IIIIII - 5<br>IIIII - 5<br>IIIII - 5<br>IIIII - 5<br>IIIII - 5<br>IIIII - 5<br>IIIIII - 5<br>IIIII - 5<br>IIIIII - 5<br>IIIIII - 5<br>IIIII - 5<br>IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII |  |
|--|--|
| I  |  |



| MT4     | 4 SERIE | S SELI | ECTION GUIDE                  |
|---------|---------|--------|-------------------------------|
| Model # | Width   | Length | Distance Between Hole Centers |
| MT4-2   | 4.00″   | 2.00″  | 2.00" Center to Center        |
| MT4-4   | 4.00″   | 4.00″  | 2.00" Center to Center        |
| MT4-6   | 4.00″   | 6.00″  | 2.00" Center to Center        |
| MT4-8   | 4.00″   | 8.00″  | 2.00" Center to Center        |
| MT4-10  | 4.00″   | 10.00″ | 2.00" Center to Center        |
| MT4-12  | 4.00″   | 12.00″ | 2.00" Center to Center        |
| MT4-18  | 4.00″   | 18.00″ | 2.00" Center to Center        |
| MT4-24  | 4.00″   | 24.00″ | 2.00" Center to Center        |
| MT4-48  | 4.00″   | 48.00″ | 2.00" Center to Center        |