

## **PRO1 SUBMITTAL SHEET**

Job Name:	Location:	Date:	
Purchaser:		_ Installer:	
Submitted to:		For: RNC R&R	Commercial

# **MODEL T855**

#### Universal

**Light Commercial / Residential** 

Up to 2 Heat, 2 Cool Conventional Up to 3 Heat, 2 Cool Heat Pump Battery or Hardwire

7 Day, 5/1/1 or Non-Programmable



#### This model features:

- 8 sq. inch display
- · Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Keypad lockout
- Adjustable setpoint limits
- Simple private label badge system
- Easy access battery compartment

- 5 Year Warranty
- Seperate heating and cooling swing (cycle rate) adjustments
- 5 minute compressor delay protection (selectable on or off)
- Universal subbase
- Battery or 24v power
- Programmable Fan

### **Specifications:**

Application Up to 2 Heat, 2 Cool Conventional - Up to 3 Heat, 2 Cool Heat Pump

Programmability 7 Day, 5/1/1 or Non-Programmable

Changeover Auto

Display Range 41°F to 95°F (5°C to 35°C) Control Range 44°F to 90°F (7°C to 32°C)

Display Accuracy +/- 1°F

Heat Swing Adjustable from 0.2°F to 2.0°F Cool Swing Adjustable from 0.2°F to 2.0°F Terminals Rc, Rh, G, Y, Y2, C, O, B, W/E, W2

Load Rating 1 amp per terminal, 1.5 amp maximum all terminals combined Power Source 18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire)

Battery power from 2 AA Alkaline batteries

Operating Ambient  $32^{\circ}F$  to  $+105^{\circ}F$  ( $0^{\circ}C$  to  $+41^{\circ}C$ ) Operating Humidity 90% non-condensing maximum

Mounting Wall or Junction Box

Dimensions 4.7"W x 4.4"H x 1.1"D (119mm W x 112mm H x 28mm D)

Warranty 5 year warranty