

# Refrigeration Condenser Fan 5.0" and 5.6" Diameter Open Drip Proof, Totally Enclosed, Air Over and Open Air Over



## APPLICATIONS:

Condenser cooling fan motors to meet manufacturer's requirements for commercial refrigeration units.

## FEATURES:

- OEM Direct Replacements
- Single Speed
- Automatic Reset Thermal Overload Protector
- Designed for use with 370V Capacitors
- **Discount Symbol: DS-3HAC**




Figure A




Figure B

## 5.0" Diameter, 5/16" Diameter Shaft

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Shaft Dia.	Mount	Ship Wt.	Notes	OEM	List
1/20	1500	230	1775P	SAB	3.0	.5	3.1	3.8	6.9	5/16"	Hub Ring	8.4	98	TE	\$148
1/15	1500	230	1779P	SAB	3.0	.62	3.1	3.8	6.9	5/16"	Hub Ring	8	98	TE	\$154

## 5.6" Permanent Split Capacitor

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Mount	Ship Wt.	Notes	OEM	List
1/6	1550	208-230	6128	SAB	5.0	9.0	2.5	4.1	7.6	Resilient	9	98, 64, H36	CO	\$263
	1550	208-230	1645	Ball	3.0	1.4	2.1	3.8	6.4	Stud	11	H35	HU	\$263
	1550/1	460	1265	SAB	3	0.55	3.1	4.1	7.1	Bracket	9	98	CO	\$248
1/5	1075	208-230	1648	Ball	4.0	2.0	2.5	4.3	7.9	Stud	13	H35	HU	\$244
	1075	575	1093	Ball	4.0	.80	2.5	4.8	8.4	Stud	13	H36		\$246
1/4	1550	230	6124	SAB	5.0	2.1	3.0	4.1	7.1	Band	13	64, H36	CO	\$242
	1625	208-230	6129	SAB	5.0	1.5	2.3	4.3	7.9	Resilient	15	64, H36	CO	\$273
	1625	230	3042	Ball	4.0	1.4	1.5	5.1	7.7	Hub Ring	11	64, H4, H36	TY	\$239
	1625	230	8330	SAB	4.0	1.9	2.2	4.3	7.7	3 Lugs	12	64, 98, H36, H42	TE	\$241
	1625	380-420/460	8331	SAB	4.0	.95	2.2	4.3	7.7	3 Lugs	19	98, 64, H36, H42	TE	\$257
	1625	460	6138	SAB	5.0	0.90	3.05	4.8	7.9	Stud	14	98	CO	\$288
	1625	575	1312	SAB	-	0.7	3.1	4.8	7.9	Band	13	64, 98		\$250
1/3	1625	208-230	6127	SAB	4.0	2.2	1.75	5.8	8.7	Resilient	15	98, 64, H45	CO	\$264
	1625	208-230	7232	SAB	6.0	2.9	3.7	4.6	9.3	Hub Ring	23	64, H35	HR	\$173
	1075/2	208-230	1354	Ball	-	2.0	3.1	4.8	8.4	3 Lugs	12.1			\$239
1/2	1725	208-230	644	Ball	5.0	2.7	3.5	5.1	9.1	Stud	15	98, H18, H36	HU	\$250
	1100/1	208-230/460	4941	BALL	12.5	2.8/1.5	4.5	6.9	11.4	Resilient	16	-	-	\$350

CO = Copeland    HU = Hussmann    HR = Hill Refrigeration    TE = Tecumseh    TY = Tyler

Note 64: Capacitor Included  
 Note 98: 50/60 Hz  
 Note H4: 2-1/4" hub rings  
 Note H18: Conduit box

Note H35: Open Air Over  
 Note H36: Open Drip Proof  
 Note H42: Shaft Down  
 Note H45: Totally Enclosed, Air Over