

Armstrong Armstrong Universal Stainless Steel Connector

IS-2 Stainless Steel Connector with Integral Strainer Provides:

- A full line stainless steel strainer in the connector eliminates leak points and reduces installation time
- A strainer that is not discarded when the trap is replaced
- Easy strainer screen replacement
- · Optional blowdown valve
- Accommodates Armstrong's inverted bucket, disc, thermostatic, thermostatic wafer, bimetallic, and float and thermostatic traps.
 Any manufacturer's 2-bolt steam trap can also be applied to Armstrong's S-2 connector.

Maximum Operating Conditions

Maximum allowable pressure: 650 psig @ 600°F (45 bar @ 315°C)

Connector Styles

- IS-2 connector with integral strainer
- · IS-2 connector with integral strainer with blowdown valve

Connection Sizes

• 1/2", 3/4", 1"

Connection Types

Screwed NPT and BSPT Socketweld Flanged (consult factory)

Materials

Connector Body: Strainer:

All stainless steel—304 20 x 20 Mesh 304 stainless steel

Weight

2 lbs (0.91 kg

How to Order IS-2 Connector with Integral Strainer

Specify:

- Connection style
- Connection size
- · Connection type
- · Inlet flow direction
- Left to Right
- Right to Left



Standard 360° Stainless Steel Connector Provides:

- A compact, lightweight assembly
- Standardization, reducing inventory
- A compact design, simplifying piping
- Accommodates Armstrong's inverted bucket, disc, thermostatic, thermostatic wafer and bimetallic steam traps. Any manufacturer's 2-bolt steam trap can also be applied to Armstrong's standard connector.

Maximum Operating Conditions

Maximum allowable pressure: 650 psig @ 600°F (45 bar @ 315°C)

Connector Styles

• Standard 360°

Connection Sizes

• 1/2", 3/4"

Connection Types

Screwed NPT and BSPT Socketweld Flanged (consult factory)

Weight

1-1/2 lbs (0.70 kg)

How to Order Standard 360° Stainless Steel Connector

Specify:

- Connection size
- Connection type

